



Highlights

- Up-to 22TB¹ capacity
- · Enterprise-class reliability and performance
- 5-year limited warranty⁸
- 550TB per year workload rating³
- Up-to 2.5 million hours Mean Time Between Failure (MTBF)⁴
- Innovative AllFrame™ technology helps reduce dropped frames
- Western Digital Device Analytics[™] (WDDA) proactive health management

WD Purple® Pro

Professional Grade Storage for Smart Video Recording and Al Video Analytics

WD Purple® Pro delivers ultimate reliability and performance for the most demanding video recording and analytics environments

Higher Capacity Drives for More Demanding Smart Video Solutions

WD Purple® Pro delivers big capacities up to 22TB¹ for larger scale deployments and longer-term video retention requirements.

Enterprise Class Reliability

True enterprise class drives designed with the highest level of reliability. With up to 2.5 million hours MTBF⁴ and backed with a 5-year limited warranty⁸, WD Purple® Pro is built for high-end video recorders and analytics servers.

High Performance for Simultaneous Video Recording and Real-Time Al Analysis

WModern cameras and Al-enabled recording systems send multiple streams of high-definition video, picture files and metadata to storage. WD Purple® Pro drives deliver our highest level of performance to accurately store all streams

Built for Advanced Smart Video Workloads

WD Purple® Pro delivers higher workload capability up-to 550TB/year³. Keep up with heavy video data capture and AI analysis found in advanced video management systems

Innovative AllFrame[™] Technology

AllFrame™ technology intelligently guides video, picture and meta data streams to disk while helping to reduce dropped video frames

Proactive Drive Health Insights with WDDA™

Western Digital Device Analytics™ (WDDA) monitors drive health and recommends action to improve drive operation. Requires compatible video recorder or system.

PRODUCT BRIEF SURVEILLANCE HARD DRIVES

Specifications

	22TB1	18TB1	14TB ¹	12TB1	10TB1	8TB ¹
Model Number	WD221PURP	WD181PURP	WD142PURP	WD121PURP	WD101PURP	WD8002PURP
Formatted capacity ¹	22TB	18TB	14TB	12TB	10TB	8TB
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Advanced Format (AF)	Yes	Yes	Yes	Yes	Yes	Yes
Recording technology	CMR	CMR	CMR	CMR	CMR	CMR
RoHS compliant ⁵	Yes	Yes	Yes	Yes	Yes	Yes
Product Features						
Cameras supported	Up to 64 HD ²					
Al streams	32	32	32	32	32	32
Firmware feature name	AllFrame Al					
Tarnish resistant components	Yes	Yes	Yes	Yes	Yes	Yes
Performance		,				
Interface transfer rate (max) Buffer to host Host to/from drive (sustained) ⁶	6 Gb/s 265 MB/s	6 Gb/s 272 MB/s	6 Gb/s 255 MB/s	6 Gb/s 245 MB/s	6 Gb/s 265 MB/s	6 Gb/s 267 MB/s
Cache (MB) ¹	512	512	512	256	256	256
RPM	7200	7200	7200	7200	7200	7200
Reliability/Data Entigrity						
Load/unload cycles ⁷	600,000	600,000	600,000	600,000	600,000	600,000
Annualized workload rating ³	Up to 550 TB/yr	Up to 550 TB/year	Up to 550 TB/yea			
Non-recoverable read errors per bits read	<1 in 10^15					
MTBF⁴	2,500,000	2,500,000	2,500,000	2,500,000	2,000,000	2,000,000
Limited Warranty (years)8	5	5	5	5	5	5
Power Management						
Average power requirements (W) Read/write Idle Standby and sleep	6.9 5.6 1.2	6.3 5.9 0.9	6.6 5.7 0.9	6.6 5.6 0.6	9 8 0.5	7.3 6.5 0.3
Environmental specifications						
Temperature Operating Non-operating	0°C to 65°C -40°C to 70°C					
Shock (Gs) Operating Operating Non-operating	40 40 200	50 50 250	50 50 250	30 65 250	70 70 250	30 65 250
Acoustics (dBA) Idle Seek (average	20 32	20 27	20 27	20 29	34 38	27 29
Physical Dimensions						
Height (in/mm, max)	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1
Length (in/mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in/mm, ± .01in)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb/kg, ± 3%)	1.48/0.67	1.52/0.69	1.52/0.69	1.46/0.66	1.65/0.75	1.58/0.715

¹ 1MB = one million bytes, 1GB = one billion bytes, and 1TB = one trillion bytes. 1TB = one trillion bytes. Actual user capacity may be less, depending on operating environment.

² Single stream per camera @ 3.2Mbps (1080p, H.265, 25 fps). Results may vary depending on camera resolution, file

😘 . Western Digital.

©2024 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital design, the Western Digital logo, AllFrame, OptiNAND, WD Purple, WDDA, and Western Digital Device Analytics are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. All other marks are the property of their respective owners. Product specifications subject to change without notice. Pictures shown may vary from actual products.

Single stream per camera @ 3.2Mbps (1080p, H.265, 25 tps). Results may vary depending on camera resolution, to format, frames per second, software, system settings, video quality, and other factors.

³ Workload Rate is defined as the amount of user data transferred to or from the hard drive. Workload Rate is annualized (TB transferred X (8760 / recorded power-on hours)). Workload Rate will vary depending on your hardware and software composition.

⁶ Projected values. When final, MTBF specifications will be based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions, workload of 220TB/year, and drive temperature of 40°C. Derating of MTBF will occur above these parameters, up to 550TB writes per year, and 65°C drive temperature. MTBF ratings do not predict an individual drive's reliability and do not constitute a warranty. ⁵ This drive is in compliance with the European Union Directive 2011/65/EU and Directive (EU) 2015/863 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

⁵ WD hard drive products manufactured and sold worldwide after June 8, 2011, meet or exceed Restriction of

Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

Lin to stated speed 1 MB/s = 1 million bytes per second. Rased on internal testing: performance may vary den

⁶ Up to stated speed. 1 MB/s = 1 million bytes per second. Based on internal testing; performance may vary depending upon host device, usage conditions, drive capacity, and other factors.

⁷ Controlled unload at ambient condition

⁸ See support.wdc.com/warranty for regional specific warranty details.